



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Material name AKWASEAL™ UVA
Version # 05
Revision date 24-February-2011
Chemical description Liquid
CAS # Mixture
Manufacturer information CETCO
Building Materials Group
2870 Forbs Avenue
Hoffman Estates, IL 60192 US
safety.data@amcol.com
<http://www.cetco.com/>
General Information (800) 527-9948
CHEMTREC® (800) 424-9300

2. Hazards Identification

Emergency overview Irritating to eyes, respiratory system and skin. May cause sensitization by inhalation and skin contact. Prolonged or repeated exposure increases the risk.

Potential health effects

Routes of exposure Inhalation. Skin contact.

Eyes Irritating to eyes. Symptoms include itching, burning, redness and tearing.

Skin Substance causes moderate skin irritation. May cause sensitization by skin contact.

Inhalation May cause irritation of respiratory tract. May cause sensitization by inhalation.

Ingestion Irritating to mouth, throat, and stomach. Ingestion of this product may cause nausea, vomiting and diarrhea.

Signs and symptoms Cough. Discomfort in the chest. Shortness of breath.

3. Composition / Information on Ingredients

Components	CAS #	Percent
4,4'-DIPHENYLMETHANE DIISOCYANATE	101-68-8	15 - 40
1,1'-Methylenebis (isocyanato-) benzene	26447-40-5	10 - 30
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	9016-87-9	10 - 30

Composition comments This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 20 minutes. Get medical attention if irritation develops or persists.

Skin contact Wash off immediately with plenty of water. Remove and isolate contaminated clothing and shoes. Get medical attention if irritation develops or persists.

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. Get medical attention immediately.

Ingestion If material is ingested, immediately contact a physician or poison control center. Do not induce vomiting without medical advice. If swallowed, rinse mouth with water (only if the person is conscious).

Notes to physician Symptoms may be delayed. Keep under medical supervision for at least 48 hours. Provide general supportive measures and treat symptomatically.

General advice Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire Fighting Measures

Flammable properties Containers may explode when heated.

Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Alcohol foam. Water spray. Dry chemical. Foam.

Protection of firefighters

Protective equipment for firefighters

In the event of fire, wear self-contained breathing apparatus.

Fire fighting equipment/instructions

Move containers from fire area if you can do it without risk. Do not scatter spilled material with high pressure water streams. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. ALWAYS stay away from tanks engulfed in flame. Cool containers with flooding quantities of water until well after fire is out.

Specific methods

In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers.

6. Accidental Release Measures

Personal precautions

Ensure adequate ventilation. Use personal protective equipment. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak.

Environmental precautions

Prevent further leakage or spillage if safe to do so.

Methods for containment

Stop leak if you can do so without risk. Dike the spilled material, where this is possible.

Methods for cleaning up

Dike far ahead of liquid spill for later disposal. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. After removal flush contaminated area thoroughly with water. Ventilate the contaminated area.

7. Handling and Storage

Handling

Wash hands after handling and before eating. When using do not eat or drink. Avoid contact with skin and eyes. Do not get this material in your eyes, on your skin, or on your clothing. Do not handle or store near an open flame, heat or other sources of ignition.

Storage

Keep locked-up. Keep out of the reach of children. Keep this material away from food, drink and animal feed. Keep containers tightly closed in a dry, cool and well-ventilated place. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Keep away from heat, sparks, and flame.

8. Exposure Controls / Personal Protection

Occupational exposure limits

Canada - British Columbia

Components

Components	Type	Value
4,4'-DIPHENYLMETHANE DIISOCYANATE (101-68-8)	Ceiling	0.0100 ppm
	TWA	0.0050 ppm

Canada - Ontario

Components

Components	Type	Value
4,4'-DIPHENYLMETHANE DIISOCYANATE (101-68-8)	Ceiling	0.8000 micromoles/m ³
		0.0200 ppm
	TWA	0.2000 micromoles/m ³
		0.0050 ppm

Canada - Quebec

Components

Components	Type	Value
4,4'-DIPHENYLMETHANE DIISOCYANATE (101-68-8)	TWA	0.0050 ppm
		0.0510 mg/m ³

Engineering controls

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. If these are not sufficient to maintain concentrations of particulates and solvent vapor below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Eye / face protection

Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Where contact is likely, wear chemical-resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield. Use of butyl rubber or nitrile gloves is recommended

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

9. Physical & Chemical Properties

Appearance	Not available.
Color	Clear to light yellow.
Odor	Slightly. Musty.
Odor threshold	Not available.
Physical state	Not available.
Form	Liquid.
pH	Not available.
Melting point/Freezing point	Not available.
Boiling point	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability limits in air, upper, % by volume	Not available.
Flammability limits in air, lower, % by volume	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Specific gravity	Not available.
Relative density	0.3994 lb/cu ft estimated
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	300 - 500 cps

10. Chemical Stability & Reactivity Information

Chemical stability	Stable at normal conditions. No hazards to be especially mentioned.
Conditions to avoid	Direct sources of heat. Keep away from water.
Incompatible materials	This product may react with strong oxidizing agents. Reaction with water may generate much heat which will increase the concentration of fumes in the air.
Hazardous decomposition products	Upon decomposition, this product may yield gaseous nitrogen oxides, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. and hydrogen cyanide (hydrocyanic acid)
Possibility of hazardous reactions	Hazardous polymerization can occur with elevated temperatures. Hazardous polymerization can occur with contact with alkalies. Hazardous polymerization can occur with metallic catalysts.

11. Toxicological Information

Toxicological data

Product

AKWASEAL™ UVA (Mixture)

Test Results

Acute Dermal LD50 Rabbit: 28019 mg/kg estimated
Acute Dermal LD50 Rat: 28019 mg/kg
Acute Inhalation LC50 Rat: 4 mg/l/4h
Acute Inhalation LC50 Rat: 1.8725 mg/l estimated
Acute Oral LD50 Rat: 12498 mg/kg

Components

4,4'-DIPHENYLMETHANE DIISOCYANATE (101-68-8)

Test Results

Acute Inhalation LC50 Rat: 0.369 mg/l 4.00 Hours
Acute Oral LD50 Rat: 9200 mg/kg
Acute Dermal LD50 Rabbit: 6200 mg/kg
Acute Inhalation LC50 Rat: 0.369 mg/l/4h
Acute Dermal LD50 Rabbit: 9400 mg/kg

1,1'-Methylenebis (isocyanato-) benzene (26447-40-5)

POLYMETHYLENE POLYPHENYLENE ISOCYANATE (9016-87-9)

Components	Test Results
POLYMETHYLENE POLYPHENYLENE ISOCYANATE (9016-87-9)	Acute Inhalation LC50 Rat: 490 mg/l/4h Acute Oral LD50 Rat: 49000 mg/kg
Sensitization	May cause sensitization by inhalation and skin contact.
Local effects	Harmful by inhalation. Irritating to respiratory system and skin.
Chronic effects	Repeated or prolonged contact causes sensitization, asthma and eczemas. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.
Carcinogenicity	Not listed by ACGIH, IARC, NIOSH, NTP OR OSHA.
IARC Monographs. Overall Evaluation of Carcinogenicity	
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)	3 Not classifiable as to carcinogenicity to humans.
POLYMETHYLENE POLYPHENYLENE ISOCYANATE (CAS 9016-87-9)	3 Not classifiable as to carcinogenicity to humans.
Mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Further information	Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates.

12. Ecological Information

Ecotoxicological data	Test Results
Product	
AKWASEAL™ UVA (Mixture)	EC50 Daphnia: >= 1000 mg/l 24.00 Hours LC50 Fish: >= 1000 mg/l
Ecotoxicity	Components of this product have been identified as having potential environmental concerns.
Environmental effects	We have no quantitative data concerning the ecological effects of this product.
Persistence and degradability	Not available.

13. Disposal Considerations

Disposal instructions Dispose in accordance with all applicable regulations.

14. Transport Information

TDG

Not regulated as dangerous goods.

15. Regulatory Information

Canadian regulations	This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.
WHMIS status	Controlled
WHMIS classification	D1A - Immediate/Serious-VERY TOXIC D2A - Other Toxic Effects-VERY TOXIC D2B - Other Toxic Effects-TOXIC

WHMIS labeling



Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information


Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

Further information This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

HMIS ratings

HEALTH		*	3
FLAMMABILITY			1
PHYSICAL HAZARD			1
PERSONAL PROTECTION			

NFPA ratings



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and completeness of such information for each particular use.

Third party materials: Insofar as materials not manufactured or supplied by this manufacturer are used in conjunction with, or instead of this product, it is the responsibility of the customer to obtain, from the manufacturer or supplier, all technical data and other properties relating to these and other materials and to obtain all necessary information relating to them. No liability can be accepted in respect of the use of this product in conjunction with materials from another supplier. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Issue date 24-February-2011