

SAFETY DATA SHEET

1. Identification

Product identifier CoreFlex Universal Corners

Other means of identification Not available. Recommended use Not available. None known. **Recommended restrictions**

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name CETCO, an MTI Company **Address** 2870 Forbs Avenue

Hoffman Estates, IL 60192

United States

General Information 800 527-9948 **Telephone**

Website http://www.cetco.com/ safety.data@amcol.com E-mail

Emergency phone number

1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962 Access Code 333562 **Americas**

2. Hazard(s) identification

Physical hazards Not classified. Not classified. **Health hazards Environmental hazards** Not classified. **OSHA** defined hazards Not classified.

Label elements

Hazard symbol None.

Not available. Signal word **Hazard statement** Not available. Prevention Not available. Response Not available. Storage Not available. Disposal Not available.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
CALCIUM CARBONATE	CALCIUM CARBONATE PRECIPITATED CALCIUM CARBONATE (PCC)	471-34-1	30.0057131974
Ethene, chloro-, homopolymer		9002-86-2	30.0057131974
Tin		7440-31-5	5.0009521995
Arsenic		7440-38-2	< 0.3
Benzene		71-43-2	< 0.3
Lead		7439-92-1	< 0.2
2-Pentanone, 4-methyl-		108-10-1	< 0.1
Carbon disulfide		75-15-0	< 0.1
Other components below reportat	ole levels		30 - < 40

Not applicable to consumer products. **Composition comments**

Material name: CoreFlex Universal Corners

SDS US

4. First-aid measures

Inhalation Call a physician if symptoms develop or persist.

Not available.

Skin contact Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Ingestion Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.

Most important

symptoms/effects, acute and

delayed

General information If you feel unwell, seek medical advice (show the label where possible). Show this safety data

sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Not available.

Water.

Specific hazards arising from

the chemical

Not applicable.

Not available.

Special protective equipment and precautions for firefighters

Fire-fighting equipment/instructions

Specific methods

In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers.

In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers.

Cool containers exposed to flames with water until well after the fire is out.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material. Keep people away from and upwind of spill/leak. Keep upwind. Keep out of low areas. Avoid inhalation of dust from the spilled material. Wear a dust mask if dust is generated above exposure limits.

Methods and materials for containment and cleaning up

This product is miscible in water. Dike far ahead of spill for later disposal. If sweeping of a contaminated area is necessary use a dust suppressant agent which does not react with the product. Sweep up or vacuum up spillage and collect in suitable container for disposal. Collect dust using a vacuum cleaner equipped with HEPA filter. Avoid dust formation. Avoid the generation of dusts during clean-up. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling

In case of insufficient ventilation, wear suitable respiratory equipment. Provide appropriate exhaust

ventilation at places where dust is formed. Practice good housekeeping.

Conditions for safe storage, including any incompatibilities Store in a well-ventilated place. Keep away from heat, sparks, and flame. No special restrictions on storage with other products.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Туре	Value	
Arsenic (CAS 7440-38-2)	TWA	0.01 mg/m3	
Benzene (CAS 71-43-2)	STEL	5 ppm	
	TWA	1 ppm	
Ethene, chloro-, homopolymer (CAS 9002-86-2)	STEL	5 ppm	
	TWA	1 ppm	
Lead (CAS 7439-92-1)	TWA	0.05 mg/m3	
US. OSHA Table Z-1 Limits for Air	Contaminants (29 CFR 1910.	1000)	
Components	Туре	Value	
2-Pentanone, 4-methyl- (CAS 108-10-1)	PEL	410 mg/m3	
•		100 ppm	
Tin (CAS 7440-31-5)	PEL	2 mg/m3	

Material name: CoreFlex Universal Corners

6618 Version #: 03 Revision date: 07-May-2015 Print date: 07-May-2015

Additional components	Туре	Value	Form
NERT OR NUISANCE DUSTS	PEL	5 mg/m3	Respirable fraction.
(CAS SEQ250)			
,		15 mg/m3	Total dust.
US. OSHA Table Z-2 (29 CFR 1910.1000)			
Components	Туре	Value	
Benzene (CAS 71-43-2)	Ceiling	25 ppm	
,	TWA	10 ppm	
Carbon disulfide (CAS	Ceiling	30 ppm	
75-15-0)	•		
	TWA	20 ppm	
US. OSHA Table Z-3 (29 CFR 1910.1000)			_
Additional components	Туре	Value	Form
INERT OR NUISANCE	TWA	5 mg/m3	Respirable fraction.
DUSTS		Ŭ	•
(CAS SEQ250)		, <u>.</u>	-
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Values			_
Components	Туре	Value	Form
2-Pentanone, 4-methyl-	STEL	75 ppm	
(CAS 108-10-1)			
	TWA	20 ppm	
Arsenic (CAS 7440-38-2)	TWA	0.01 mg/m3	
Benzene (CAS 71-43-2)	STEL	2.5 ppm	
	TWA	0.5 ppm	
Carbon disulfide (CAS 75-15-0)	TWA	1 ppm	
Ethene, chloro-,	TWA	1 mg/m3	Respirable fraction.
nomopolymer (CAS 9002-86-2)		•	·
Lead (CAS 7439-92-1)	TWA	0.05 mg/m3	
Гin (CAS 7440-31-5)	TWA	2 mg/m3	
JS. NIOSH: Pocket Guide to Chemical Ha	zards	-	
Components	Туре	Value	Form
2-Pentanone, 4-methyl-	STEL	300 mg/m3	
CAS 108-10-1)		·	
		75 ppm	
	TWA	205 mg/m3	
		50 ppm	
Arsenic (CAS 7440-38-2)	Ceiling	0.002 mg/m3	
Benzene (CAS 71-43-2)	STEL	1 ppm	
•	TWA	0.1 ppm	
CALCIUM CARBONATE (CAS 471-34-1)	TWA	5 mg/m3	Respirable.
ONO 47 1-34-1)		10 mg/m3	Total
Carbon disulfide (CAS	STEL	30 mg/m3	Total
Carbon disulfide (CAS 75-15-0)	SIEL	อบ mg/ma	
- /		10 ppm	
	TWA	3 mg/m3	
		1 ppm	
Lead (CAS 7439-92-1)	TWA	0.05 mg/m3	
Tin (CAS 7440-31-5)	TWA	2 mg/m3	
IIII (CAS /440-31-3)	IVVA	∠ mg/m3	

Biological limit values

ACGIH Biological Expo	osure Indices
------------------------------	---------------

Components	Value	Determinant	Specimen	Sampling Time	
2-Pentanone, 4-methyl- (CAS 108-10-1)	1 mg/l	Methyl isobutyl ketone	Urine	*	
Arsenic (CAS 7440-38-2)	35 µg/l	Inorganic arsenic, plus methylated metabolites, as As	Urine	*	
Benzene (CAS 71-43-2)	25 μg/g	S-Phenylmerca pturic acid	Creatinine in urine	*	
Carbon disulfide (CAS 75-15-0)	0.5 mg/g	2-Thiothiazolidi ne-4-carboxylic acid (TTCA)	Creatinine in urine	*	
Lead (CAS 7439-92-1)	300 μg/l	Lead	Blood	*	

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Benzene (CAS 71-43-2)

Car be absorbed through the skin.

Carbon disulfide (CAS 75-15-0)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Carbon disulfide (CAS 75-15-0) Skin designation applies.

US - Tennesse OELs: Skin designation

Carbon disulfide (CAS 75-15-0)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Benzene (CAS 71-43-2)

Can be absorbed through the skin.

Carbon disulfide (CAS 75-15-0)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Carbon disulfide (CAS 75-15-0)

Can be absorbed through the skin.

Appropriate engineering

controls

Ventilation should be sufficient to effectively remove and prevent buildup of any dusts or fumes that may be generated during handling or thermal processing. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes. Use tight fitting goggles if dust is generated. Wear safety glasses with

side shields (or goggles). Eye wash fountain is recommended.

Hand protection Not normally needed.

Other Normal work clothing (long sleeved shirts and long pants) is recommended.

Respiratory protection Wear respirator with dust filter. Use a NIOSH/MSHA approved respirator if there is a risk of

exposure to dust/fume at levels exceeding the exposure limits.

Thermal hazards Not available.

General hygiene considerations

Do not breathe dust. Avoid contact with eyes. Handle in accordance with good industrial hygiene

and safety practice.

9. Physical and chemical properties

Appearance Opaque. Powder.

Physical state Solid.

Form Solid. Powder.
Color Various.
Odor Slight.

Odor threshold Not available.
pH Not available.

Melting point/freezing point 449.42 °F (231.9 °C) estimated Initial boiling point and boiling 4544.6 °F (2507 °C) estimated

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

<u>(%)</u>

Material name: CoreFlex Universal Corners

6618 Version #: 03 Revision date: 07-May-2015 Print date: 07-May-2015

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0 hPa estimated
Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Negligible

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 1166 °F (630 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Density 2.29 g/cm3 estimated
Specific gravity 2.29 estimated
1.1 - 1.6

10. Stability and reactivity

Reactivity Not available.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

Not available.

Conditions to avoid Avoid spread of dust.

Incompatible materialsNot available.Hazardous decompositionIrritants.

products

11. Toxicological information

Information on likely routes of exposure

Ingestion Not available.

Inhalation Inhalation of dusts may cause respiratory irritation.

Skin contact Not available.

Eye contact May be irritating to eyes.

Symptoms related to the physical, chemical and toxicological characteristics

Not available.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
2-Pentanone, 4-methyl- (CA	AS 108-10-1)	
Acute		
Dermal		
LD50	Rabbit	> 16000 mg/kg
Inhalation		
LC50	Rat	8.2 mg/l, 4 Hours
Oral		
LD50	Rat	2080 mg/kg
Other		
LD50	Guinea pig	0.919 ml/kg
	Mouse	590 mg/kg
	Rat	1.14 ml/kg

Material name: CoreFlex Universal Corners

Components	Species	Test Results
Arsenic (CAS 7440-38-2)		
Acute		
Oral		
LD50	Mouse	145 mg/kg
	Rat	763 mg/kg
Other		
LD50	Mouse	46.2 mg/kg
	Rat	13.39 mg/kg
Benzene (CAS 71-43-2)		
Acute		
Inhalation		
LC50	Mouse	9980 ppm
	Rat	10000 ppm, 7 Hours
Oral		
LD50	Mouse	4700 mg/kg
	Rat	3306 mg/kg
Other		
LD50	Mouse	340 mg/kg
		0.28 ml/kg
	Rat	2.89 mg/kg
CALCIUM CARBONATE (C	AS 471-34-1)	
Acute		
Oral		
LD50	Mouse	6450 mg/kg
	Rat	6450 mg/kg
Carbon disulfide (CAS 75-1	5-0)	
Acute		
Inhalation		
LC50	Mouse	10 mg/l, 2 Hours
		0.69 mg/l, 1 Hours
	Rabbit	16 mg/l, 6 Hours
	Rat	25 mg/l, 2 Hours
Oral		
LD50	Guinea pig	2125 mg/kg
	Mouse	2780 mg/kg
	Rat	3188 mg/kg
Other		· -
LD50	Mouse	1890 mg/kg
	Rat	583 mg/kg

^{*} Estimates for product may be based on additional component data not shown

Skin corrosion/irritation Not available.

Serious eye damage/eye

irritation

Dust in the eyes will cause irritation. May be irritating to eyes.

Respiratory or skin sensitization

Respiratory sensitizationNot available.Skin sensitizationNot available.Germ cell mutagenicityNot available.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

2-Pentanone, 4-methyl- (CAS 108-10-1) 2B Possibly carcinogenic to humans.

Arsenic (CAS 7440-38-2) 1 Carcinogenic to humans. Benzene (CAS 71-43-2) 1 Carcinogenic to humans.

Ethene, chloro-, homopolymer (CAS 9002-86-2) 3 Not classifiable as to carcinogenicity to humans.

Lead (CAS 7439-92-1) 2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Arsenic (CAS 7440-38-2) Known To Be Human Carcinogen. Benzene (CAS 71-43-2) Known To Be Human Carcinogen.

Lead (CAS 7439-92-1) Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Arsenic (CAS 7440-38-2) Cancer Benzene (CAS 71-43-2) Cancer Ethene, chloro-, homopolymer (CAS 9002-86-2) Cancer

Reproductive toxicity Specific target organ toxicity - Not available.

single exposure

Not available.

Specific target organ toxicity -

Not available.

repeated exposure

Not available.

Aspiration hazard Chronic effects

Components

Not expected to be hazardous by WHMIS criteria.

Species

Further information This product has no known adverse effect on human health.

12. Ecological information

Ecotoxicity

Components		Opecies	i est ivesuits
2-Pentanone, 4-methyl- (CA	AS 108-10-1)		
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	492 - 593 mg/l, 96 hours
Arsenic (CAS 7440-38-2)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	9.9 mg/l, 96 hours
Benzene (CAS 71-43-2)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	8.76 - 15.6 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	7.2 - 11.7 mg/l, 96 hours
CALCIUM CARBONATE (C	AS 471-34-1)		
Aquatic			
Fish	LC50	Western mosquitofish (Gambusia affinis)	> 56000 mg/l, 96 hours
Carbon disulfide (CAS 75-1	5-0)		
Fish	LC50	Fish	4 mg/L, 96 Hours
Aquatic			
Fish	LC50	Guppy (Poecilia reticulata)	3 - 5.8 mg/l, 96 hours
Lead (CAS 7439-92-1)			
Fish	LC50	Fish	6.5 mg/L, 96 Hours
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	1.17 mg/l, 96 hours

Test Results

Persistence and degradability Not available. **Bioaccumulative potential** Not available. Partition coefficient n-octanol / water (log Kow)

2-Pentanone, 4-methyl-1.31 Renzene 2 13 1.94 Carbon disulfide

Mobility in soil Not available. Not available. Other adverse effects

6618 Version #: 03 Revision date: 07-May-2015 Print date: 07-May-2015

^{*} Estimates for product may be based on additional component data not shown.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Dispose in accordance with all applicable regulations.

Hazardous waste code Not regulated.

US RCRA Hazardous Waste P List: Reference

P022 Carbon disulfide (CAS 75-15-0)

US RCRA Hazardous Waste U List: Reference

2-Pentanone, 4-methyl- (CAS 108-10-1) U161 Benzene (CAS 71-43-2) U019

Waste from residues / unused

Not applicable.

products

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not available.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

CERCLA/SARA Hazardous Substances - Not applicable.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-Pentanone, 4-methyl- (CAS 108-10-1) LISTED Arsenic (CAS 7440-38-2) LISTED Benzene (CAS 71-43-2) LISTED Carbon disulfide (CAS 75-15-0) LISTED Lead (CAS 7439-92-1) LISTED

US EPCRA Section 304 Extremely Haz. Subs. & CERCLA Haz. Subs.: Section 304 EHS reportable quantity

Carbon disulfide (CAS 75-15-0) US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Arsenic (CAS 7440-38-2) Cancer Benzene (CAS 71-43-2) Cancer Ethene, chloro-, homopolymer (CAS 9002-86-2) Cancer

Lead (CAS 7439-92-1) Reproductive toxicity

Arsenic (CAS 7440-38-2) Liver

Benzene (CAS 71-43-2) Central nervous system Ethene, chloro-, homopolymer (CAS 9002-86-2) Central nervous system Lead (CAS 7439-92-1) Central nervous system

Arsenic (CAS 7440-38-2) Skin Benzene (CAS 71-43-2) Blood Ethene, chloro-, homopolymer (CAS 9002-86-2) Liver Lead (CAS 7439-92-1) Kidney

Arsenic (CAS 7440-38-2) Respiratory irritation

Benzene (CAS 71-43-2) Aspiration Blood Ethene, chloro-, homopolymer (CAS 9002-86-2) Lead (CAS 7439-92-1) Blood

Arsenic (CAS 7440-38-2) Nervous system

Benzene (CAS 71-43-2) Ethene, chloro-, homopolymer (CAS 9002-86-2) Flammability Lead (CAS 7439-92-1) Acute toxicity Arsenic (CAS 7440-38-2) Acute toxicity

Benzene (CAS 71-43-2) Eye

respiratory tract irritation

Material name: CoreFlex Universal Corners

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely

Yes

hazardous substance SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Arsenic	7440-38-2	< 0.3	
Benzene	71-43-2	< 0.3	
Lead	7439-92-1	< 0.2	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

2-Pentanone, 4-methyl- (CAS 108-10-1)

Arsenic (CAS 7440-38-2) Benzene (CAS 71-43-2) Carbon disulfide (CAS 75-15-0)

Lead (CAS 7439-92-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Carbon disulfide (CAS 75-15-0)

Safe Drinking Water Act

Not regulated.

(SDWA)

DEA Essential Chemical Code Number

2-Pentanone, 4-methyl- (CAS 108-10-1) 6715

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

2-Pentanone, 4-methyl- (CAS 108-10-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

2-Pentanone, 4-methyl- (CAS 108-10-1) 6715

US state regulations

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US - Pennsylvania RTK - Hazardous Substances: Listed substance

2-Pentanone, 4-methyl- (CAS 108-10-1)

Arsenic (CAS 7440-38-2) Benzene (CAS 71-43-2) Carbon disulfide (CAS 75-15-0) Lead (CAS 7439-92-1) Tin (CAS 7440-31-5)

US. Massachusetts RTK - Substance List

2-Pentanone, 4-methyl- (CAS 108-10-1)

Arsenic (CAS 7440-38-2) Benzene (CAS 71-43-2) Carbon disulfide (CAS 75-15-0) Lead (CAS 7439-92-1) Tin (CAS 7440-31-5)

US. New Jersey Worker and Community Right-to-Know Act

2-Pentanone, 4-methyl- (CAS 108-10-1) 500 LBS
Arsenic (CAS 7440-38-2) 500 LBS
Benzene (CAS 71-43-2) 500 LBS
Carbon disulfide (CAS 75-15-0) 500 LBS
Ethene, chloro-, homopolymer (CAS 9002-86-2) 500 LBS
Lead (CAS 7439-92-1) 500 LBS

US. Rhode Island RTK

2-Pentanone, 4-methyl- (CAS 108-10-1)

Arsenic (CAS 7440-38-2) Benzene (CAS 71-43-2) Carbon disulfide (CAS 75-15-0) Lead (CAS 7439-92-1)

US. California Proposition 65

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

2-Pentanone, 4-methyl- (CAS 108-10-1) Listed: November 4, 2011 Listed: February 27, 1987 Arsenic (CAS 7440-38-2) Benzene (CAS 71-43-2) Listed: February 27, 1987 Lead (CAS 7439-92-1) Listed: October 1, 1992

US - California Proposition 65 - CRT: Listed date/Developmental toxin

2-Pentanone, 4-methyl- (CAS 108-10-1) Listed: March 28, 2014 Benzene (CAS 71-43-2) Listed: December 26, 1997 Carbon disulfide (CAS 75-15-0) Listed: July 1, 1989 Listed: February 27, 1987 Lead (CAS 7439-92-1)

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Carbon disulfide (CAS 75-15-0) Listed: July 1, 1989 Lead (CAS 7439-92-1) Listed: February 27, 1987

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Inventory name

Benzene (CAS 71-43-2) Listed: December 26, 1997 Carbon disulfide (CAS 75-15-0) Listed: July 1, 1989 Lead (CAS 7439-92-1) Listed: February 27, 1987

International Inventories

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 11-August-2014 **Revision date** 07-May-2015

Version # 03

United States & Puerto Rico

HMIS® is a registered trade and service mark of the NPCA. **Further information**

HMIS® ratings Health: 2*

Flammability: 1 Physical hazard: 0

Health: 2 NFPA ratings

Flammability: 1 Instability: 0

Disclaimer The information in the sheet was written based on the best knowledge and experience currently

available.

Material name: CoreFlex Universal Corners

10 / 10

6618 Version #: 03 Revision date: 07-May-2015 Print date: 07-May-2015

On inventory (yes/no)*

Nο

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).