MINERALS TECHNOLOGIES CETCO Alexa Balakapa Graya

SAFETY DATA SHEET

1. Identification

Product identifier RM-10® 5002

Other means of identification None.

Recommended use water supply; sewerage, waste management and remediation activities: remediation activities and

other waste management services

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name CETCO Energy Services Company, an MTI Company

Address 2870 Fords Avenue

Hoffman Estates Covington, IL 60192 United States

Telephone General Information 985 871-4700 **Website** http://www.cetcoenergyservices.com/

E-mail safetydata@mineralstech.com

Emergency phone number Emergency 1.866.519.4752/1 760 476 3962

Americas 1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Serious eye damage/eye irritation Category 1

Carcinogenicity Category 1A
Specific target organ toxicity, repeated Category 1

exposure

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes serious eye damage. May cause cancer. Causes damage to organs through prolonged or

repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective

clothing/eye protection/face protection.

Response If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. Immediately call a poison center/doctor.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Material name: RM-10® 5002 SDS US

4323 Version #: 18 Revision date: 18-June-2019 Issue date: 03-July-2015

13.04% of the mixture consists of component(s) of unknown acute oral toxicity. 19.04% of the mixture consists of component(s) of unknown acute dermal toxicity. 13.04% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 13.04% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
QUARTZ (SIO2)		14808-60-7	5 - < 10
TRADE SECRET*	*	Proprietary*	6
CRISTOBALITE		14464-46-1	1 - < 3
Other components below reportable levels			80 - < 90

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Composition comments Occu

Occupational Exposure Limits for impurities are listed in Section 8.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed
General information

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Fire fighting

equipment/instructions

Specific methods
General fire hazards

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

Material name: RM-10® 5002 sps us

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not get this material in contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	ts for Air Contaminants (29 CFR 1910.1000) Type	Value	Form
CRISTOBALITE (CAS 14464-46-1)	PEL	0.05 mg/m3	Respirable dust.
QUARTZ (SIO2) (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 (29 (CFR 1910.1000)		
Components	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Impurities	Туре	Value	Form
INERT OR NUISANCE DUSTS	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Lir	nit Values		
Components	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
•			Doonirable fraction
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
	TWA TWA	0.025 mg/m3 5 mg/m3	nespirable fraction.
14808-60-7)	TWA	•	nespirable fraction.
14808-60-7) TRADE SECRET	TWA	•	Form
14808-60-7) TRADE SECRET US. NIOSH: Pocket Guide	TWA e to Chemical Hazards	5 mg/m3	
14808-60-7) TRADE SECRET US. NIOSH: Pocket Guide Components CRISTOBALITE (CAS	TWA e to Chemical Hazards Type	5 mg/m3 Value	Form
14808-60-7) TRADE SECRET US. NIOSH: Pocket Guide Components CRISTOBALITE (CAS 14464-46-1) QUARTZ (SIO2) (CAS	TWA e to Chemical Hazards Type TWA	5 mg/m3 Value 0.05 mg/m3 0.05 mg/m3	Form Respirable dust.
14808-60-7) TRADE SECRET US. NIOSH: Pocket Guide Components CRISTOBALITE (CAS 14464-46-1) QUARTZ (SIO2) (CAS 14808-60-7)	TWA e to Chemical Hazards Type TWA TWA	5 mg/m3 Value 0.05 mg/m3 0.05 mg/m3 gredient(s).	Form Respirable dust. Respirable dust.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Exposure Limit.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical stateSolid.FormSolid.

ColorNot available.OdorNot available.Odor thresholdNot available.

pH 3.5

Melting point/freezing point 305.6 °F (152 °C) estimated Initial boiling point and boiling 639.5 °F (337.5 °C) estimated

range

Flash point 385.0 °F (196.1 °C) estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Not available.

Flammability limit - upper

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.08 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) 100 %

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 788 °F (420 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Density 1.36 g/cm3 estimated

Explosive properties Not explosive.

Flammability class Combustible IIIB estimated

Flash point class

Oxidizing properties

Not oxidizing.

Percent volatile

Specific gravity

Combustible IIIB

Not oxidizing.

0 % estimated

VOC CARB

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Powerful oxidizers. Chlorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye damage.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Permanent eve damage including blindness could result.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

CRISTOBALITE (CAS 14464-46-1)

Acute Oral

LD50 Rat > 22500 mg/kg

TRADE SECRET

<u>Acute</u>

Inhalation

LC50 Rat 7.7 mg/l/4h

Oral

LD50 Rat > 11000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

CRISTOBALITE (CAS 14464-46-1) 1 Carcinogenic to humans. QUARTZ (SIO2) (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

CRISTOBALITE (CAS 14464-46-1) Cancer QUARTZ (SIO2) (CAS 14808-60-7) Cancer US. National Toxicology Program (NTP) Report on Carcinogens

CRISTOBALITE (CAS 14464-46-1) Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

QUARTZ (SIO2) (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be **Chronic effects**

harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
TRADE SECRET			
Aquatic			
Algae	IC50	Algae	31.3 mg/L, 72 Hours
Crustacea	EC50	Daphnia	85.7 mg/L, 48 Hours
Fish	LC50	Fathead minnow (Pimephales promelas) 97 mg/l, 96 hours	
		Fish	97 mg/L, 96 Hours

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

80.0 TRADE SECRET

Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Material name: RM-10® 5002 6/8 4323 Version #: 18 Revision date: 18-June-2019 Issue date: 03-July-2015

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

TRADE SECRET (CAS Proprietary) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

CRISTOBALITE (CAS 14464-46-1)

QUARTZ (SIO2) (CAS 14808-60-7)

CRISTOBALITE (CAS 14464-46-1)

QUARTZ (SIO2) (CAS 14808-60-7)

Lung effects

lung effects

CRISTOBALITE (CAS 14464-46-1) immune system effects QUARTZ (SIO2) (CAS 14808-60-7) immune system effects

CRISTOBALITE (CAS 14464-46-1) kidney effects QUARTZ (SIO2) (CAS 14808-60-7) kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65



WARNING: This product can expose you to QUARTZ (SIO2), which is known to the State of California to cause

cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

QUARTZ (SIO2) (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

CRISTOBALITE (CAS 14464-46-1) QUARTZ (SIO2) (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date03-July-2015Revision date18-June-2019

Version # 18

HMIS® ratings Health: 3*

Flammability: 0 Physical hazard: 0

NFPA ratings Health: 3

Flammability: 0 Instability: 0

Disclaimer CETCO Energy Services Company, an MTI Company cannot anticipate all conditions under which

this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and

experience currently available.