

SLURRYDRY™ SSG

ABSORBING AGENT

A granular, low-dust inorganic mineral formula used for the solidification and stabilization of concrete-related fluids and other high solids aqueous wastes. SLURRYDRY™ SSG is made from a non-biodegradable mineral designed for use on waste that fails the Paint Filter Liquids Test (PFLT) and the Toxicity Characteristic Leaching Procedure TCLP for Heavy Metals and BTEX.



TECHNICAL SPECIFICATIONS			
CHARACTERISTICS		PARTICLE	
		US Standard Sieve Size	% Retained
Color	Beige Granular	30 mesh	37.1
Moisture Content	6-9%	50 mesh	43.2
Bulk Density (lbs/ft³)	55±2	70 mesh	11.1
Package sizes available:	50lb. bags & 2,000lb. bulk bags	100 mesh	5.7
		200 mesh	1.1
		-200 mesh	1.2
FUNCTION		TYPICAL ABSORPTION RATIO BY WEIGHT (ABSORBENT:WATER)	
Solidification of aqueous matter and sludge from concrete-related fluids with low to high solids		1:70 DI Water 1:25 Typical 1:15 2% Salts	

cetco@mineralstech.com | cetco.com | 800.527.9948

UPDATED: MARCH 2021

© 2021 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.cetco.com. CETCO accepts no responsibility for the results obtained through application of this product. CETCO reserves the right to update information without notice.

