

# LIQUISORB® 1000

## ABSORBING AGENT

A proprietary blend of granular cross-linked polyacrylate super-absorbent media and specialty modified minerals that rapidly absorbs and retains large volumes of aqueous solutions.

LIQUISORB® 1000 is ideally suited for the stabilization and solidification of wastewaters and semi-solids containing petroleum based hydrocarbons and other high molecular weight organic matter.



TECHNICAL SPECIFICATIONS			
CHARACTERISTICS		PARTICLE	
		US Standard Sieve Size	% Retained
Color	Off White	30 mesh	20
Moisture Content	6-9%	50 mesh	63
Bulk Density (lbs/ft <sup>3</sup> )	30-40	70 mesh	10
Package sizes available:	50lb. bags & 2,000lb. bulk bags	100 mesh	6
		200 mesh	1
		-200 mesh	0
FUNCTION		TYPICAL ABSORPTION RATIO BY WEIGHT (ABSORBENT:WATER)	
Solidification of aqueous solutions and semi-solids containing organic matter		1:170 DI Water 1:50 Typical 1:25 2% Salts	

cetco@mineralstech.com | cetco.com | 800.527.9948

UPDATED: DECEMBER 2020

© 2020 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit [www.cetco.com](http://www.cetco.com). CETCO accepts no responsibility for the results obtained through application of this product. CETCO reserves the right to update information without notice.

