

# LIQUISORB® 2000

## ABSORBING AGENT

A powdered, inorganic mineral formula used for the solidification and stabilization of drill fluids and other high solids aqueous wastes. LIQUISORB® 2000 is made from a non-biodegradable mineral designed for use on waste that fails the Paint Filter Liquids Test (PFLT) and the Toxicity Characteristic Leaching Procedure TCLP for Heavy Metals and BTEX.



TECHNICAL SPECIFICATIONS			
CHARACTERISTICS		PARTICLE	
		US Standard Sieve Size	% Retained
Color	Beige Powder	30 mesh	0
Moisture Content	6-9%	50 mesh	2.1
Bulk Density (lbs/ft <sup>3</sup> )	55±2	70 mesh	5.7
Package sizes available:	40lb. bags & 2,000lb. bulk bags	100 mesh	7.3
		200 mesh	17.7
		-200 mesh	67.2
		FUNCTION	
Solidification of aqueous matter and drilling fluids with low to high solids		1:1:80 DI Water 1:30 Typical 1:17 2% Salts	

cetco@mineralstech.com | cetco.com | 800.527.9948

UPDATED: DECEMBER 2020

© 2020 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit [www.cetco.com](http://www.cetco.com). CETCO accepts no responsibility for the results obtained through application of this product. CETCO reserves the right to update information without notice.

