

# RM-10<sup>®</sup> 2009

## FLOCCULANT AID

Reactive separating agent composed of minerals, pH adjusting components, and polymers. A specially blended formula designed to remove heavy metals, inks, paints, and high levels of suspended solids from wastewaters generated through printing, vibratory deburring, parts washing, and penetrant processes.



### TECHNICAL SPECIFICATIONS

CHARACTERISTICS		PARTICLE	
		US Standard Sieve Size	% Retained
Color	Light Gray	30 mesh	1.1
Moisture Content	6-9%	50 mesh	45.9
Bulk Density (lbs/ft <sup>3</sup> )	70±2	70 mesh	22.3
pH (5% dispersion):	2.5-4.5	100 mesh	13.7
Package sizes available:	50lb. bags & 2,000lb. bulk bags	200 mesh	13.3
		-200 mesh	3.7

cetco@mineralstech.com | cetco.com | 800.527.9948

UPDATED: DECEMBER 2020

© 2020 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit [www.cetco.com](http://www.cetco.com). CETCO accepts no responsibility for the results obtained through application of this product. CETCO reserves the right to update information without notice.

