

# RM-10<sup>®</sup> 5007

## FLOCCULANT AID

Reactive separating agent composed of minerals, pH adjusting components, and polymers. A specially blended high efficiency formula designed to lower pH, break emulsions and remove heavy metals, inks, paints, and high levels of suspended solids from wastewaters generated through processes such as flexo-graphic printing.



TECHNICAL SPECIFICATIONS			
CHARACTERISTICS		PARTICLE	
		US Standard Sieve Size	% Retained
Color	Light Gray	30 mesh	60.3
Moisture Content	6-9%	50 mesh	30.1
Bulk Density (lbs/ft <sup>3</sup> )	70±2	70 mesh	3.5
pH (5% dispersion):	2.5-4.0	100 mesh	1.5
Package sizes available:	50lb. bags & 2,000lb. bulk bags	200 mesh	2.1
		-200 mesh	2.5

cetco@mineralstech.com | cetco.com | 800.527.9948

UPDATED: DECEMBER 2020

© 2020 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit [www.cetco.com](http://www.cetco.com). CETCO accepts no responsibility for the results obtained through application of this product. CETCO reserves the right to update information without notice.

